

Product Description

- Special design for small-size pipeline connections
- Enlarging the upper seat and diaphragm can ensure precision and fit different pipeline connections
- Ideal for industries such as petrochemical, chemical equipment construction, sewage treatment, paper, etc.



Product Specification

Diameter

70 mm, 90 mm

Process connection

1/2", 3/4", 1", 1 1/2"

Instrument connection

1/4", 3/8", 1/2"

PT, G, NPT, M

Scale ranges

70 mm

Pressure gauge:

0 ... 2.5 bar to 0 ... 25 bar

Transmitter:

0 ... 0.01 bar to -1 ... 25 bar

90 mm

Pressure gauge:

-1 ... 0 bar to -1 ... 25 bar

Transmitter:

0 ... 0.01 bar to -1 ... 25 bar
or all other equivalent vacuum or
combined pressure and vacuum ranges

Material

Body: 304 SS, 316L SS, Hastelloy C276

Diaphragm: 316L SS, Hastelloy C276

Medium Temperature

0°C ... 80°C (standard), 81°C ... 200°C,
201°C ... 400°C

Accessories (options)


Clamp, gasket, ferrule

Others

Welded with instrument, flush port



Dimensions



Dimensions (mm)				
$\varphi 70 / 90$	①	②		③
	28	1/2"	25.2	50
	28	3/4"	25.2	50
	28	1"	50.4	50
	28	1-1/2"	50.4	50

※ Ordering information

Model / Diameter / Material / Medium Temperature / Connection location of pressure gauge/
Nominal size / Scale range / Options

For any changes to the specifications of this catalogue, the latest version shall prevail.

SIN JIA ENTERPRISE COMPANY LIMITED

TEL:+886-2-2550-4512

info@sinjiagauge.com

www.sj-gauge.com

No.3, Ln. 71, Chifeng St., Datong Dist., Taipei City 103017, Taiwan

